




# BRECY Collection

FACING STONE  
WITH JOINT



CRSOL  
ÉMOTIONS MINÉRALES

## HUES



Natural\*\*



\* Non-contractual hues  
\*\* Chromatic variations (see overleaf)

## CHARACTERISTICS

- Ashlar facing stone, fine grain, slightly distressed
- Through-coloured
- Frost-resistant

## PRODUCTS



Stone  
L. 50/55/60 x h. 30  
Thickness 2 cm  
Average weight: 41,7 kg/m<sup>2</sup>



Corner  
L. 50 x w. 20 x h. 30  
L. 55 x w. 25 x h. 30  
L. 60 x w. 30 x h. 30  
Thickness 2 cm



## CHROMATIC VARIATIONS

ORSOL products have varying degrees of shades from one hue to another. Refer to the following symbols for the degree of shade of each hue.



**Example:** the natural tone offers a richer degree of colour and patina (different shades from one stone to another) than the stone tone, which is more uniform. Variations in shade on a stone or from one stone to another inherent to the natural appearance of the products cannot be the subject of a complaint.

## INSTALLATION OF FACING STONES

Download our [technical specifications](#) to identify your substrate, find out the authorised height of installation and for installation information. Only by complying with the recommendations described in this process will you be entitled to the ORSOL [10-year product guarantee](#).



### TECHNICAL SPECIFICATIONS

Download the TECHNICAL SPECIFICATIONS at [www.orsol.fr](http://www.orsol.fr)



Link to the document library: <https://www.orsol.fr/ressources/documenttheque>

## PRECAUTIONS FOR USE

**Check the conformity of the products and their packaging immediately upon receiving them, as complaints about the appearance of the products must be made before installation. Our liability is limited solely to the replacement of defective products** (see our *General Terms and Conditions of Sale* available at [www.orsol.fr](http://www.orsol.fr)).

In order to obtain a good aesthetic rendering, it is advisable to supply your sites in one go and to mix the contents of the different packages and pallets during their use; this mixture will reinforce the natural appearance of the products by harmonizing the colours and shades.

## MAINTENANCE

Neomineral is a material of 99% mineral origin, which lives, breathes, and perspires according to its environment. To provide the facing stones with lasting protection, it is essential to **apply a water-repellent product** to limit the impact of external aggression. This treatment should be applied to a clean, dry product after installation, and may need to be **renewed every 5 years**.

*Do not use high-pressure or steam cleaners, including all accessories (rotating nozzle, brush...) that may degrade the surface condition of the products.*



## CONSUMPTION OF INSTALLATION PRODUCTS

- **GLUE:** ORFLEX Hautes Performances: **6 kg/m<sup>2</sup>** indoors and **7 to 8 kg/m<sup>2</sup>** outdoors
- **JOINT:** Wall Joint Mortar: **2,5 kg/m<sup>2</sup>**
- **PROTECTION:** Water-repellent (outdoors or in damp rooms): **9 m<sup>2</sup>/L**

*Information given for guidance only for the selected collection of facing stones.  
For more details: [www.orsol.fr](http://www.orsol.fr)*



BIT.LY/ORSOL-TUTO-POSE-CAUSSE

## LAYOUT OF THE BRECY COLLECTION



1 I install white crossing the joints from one row to the next



2 I complete the joints



3 I brush and apply water-repellent

**Layout** = Way of arranging the facing stone elements to obtain a harmonious whole.

### LAYOUT OF CORNERS:

- The corners must be installed **before** the facing stone. They must be glued at a rate of 1 linear metre per day.
- Glue the corners from bottom to top, swapping short and long sides from one row to the next and leaving a joint of 1 to 2 cm between each corner.

### LAYOUT OF FACING STONES:

- Glue the stones from bottom to top in rows 2 or 3 high, criss-crossing the stones from one row to the next to avoid vertical joints and leaving a space of 1 to 2 cm between the stones.
- Continue the facing stone wall along its entire length in the same way.
- Proceed with the jointing



## TO ORDER

	Reference	Packaging		Average weight (kg)	
		Package	Pallet	Package	Pallet
Facing stone	Natural PB5	1 package (± 0,5 m <sup>2</sup> )*	64 packages (± 32 m <sup>2</sup> )	21,30	1385
Corner	PAB5	1 package (± 0,9 ml)	18 packages	32	592

\* joint included of ± 2 cm

NOTE: We recommend that you supply the site all at once to ensure uniformity of the hues.