




# OLYMPE Collection

FACING STONE  
WITHOUT JOINT



CRSOL  
ÉMOTIONS MINÉRALES

## HUES



Natural\*\*



Clay earth\*\*



## PRODUCTS



Facing stone  
L. 10 to 30 x h.5/10/15  
Thickness 2/3/4 cm  
Average weight: 48,9 kg/m<sup>2</sup>

Corner  
L. 15/20/30 x l. 10/15/20 x h. 5/10/15  
Thickness 2/3/4 cm

\* Non-contractual hues

\*\* Chromatic variations (see overleaf)

## CHARACTERISTICS

- Stone to stone facing, dry stone appearance, marked reliefs
- Through-coloured
- Frost-resistant



## CHROMATIC VARIATIONS

ORSOL products have varying degrees of shades from one hue to another. Refer to the following symbols for the degree of shade of each hue.



**Example:** the natural tone offers a richer degree of colour and patina (different shades from one stone to another) than the stone tone, which is more uniform. Variations in shade on a stone or from one stone to another inherent to the natural appearance of the products cannot be the subject of a complaint.

## INSTALLATION OF FACING STONES

Download our [technical specifications](#) to identify your substrate, find out the authorised height of installation and for installation information. Only by complying with the recommendations described in this process will you be entitled to the ORSOL [10-year product guarantee](#).



### TECHNICAL SPECIFICATIONS

Download the TECHNICAL SPECIFICATIONS at [www.orsol.fr](http://www.orsol.fr)



Link to the document library: <https://www.orsol.fr/ressources/documenttheque>

## PRECAUTIONS FOR USE

**Check the conformity of the products and their packaging immediately upon receiving them, as complaints about the appearance of the products must be made before installation. Our liability is limited solely to the replacement of defective products** (see our *General Terms and Conditions of Sale* available at [www.orsol.fr](http://www.orsol.fr)).

In order to obtain a good aesthetic rendering, it is advisable to supply your sites in one go and to mix the contents of the different packages and pallets during their use; this mixture will reinforce the natural appearance of the products by harmonizing the colours and shades.

## MAINTENANCE

Neomineral is a material of 99% mineral origin, which lives, breathes, and perspires according to its environment. To provide the facing stones with lasting protection, it is essential to **apply a water-repellent product** to limit the impact of external aggression. This treatment should be applied to a clean, dry product after installation, and may need to be **renewed every 5 years**.

*Do not use high-pressure or steam cleaners, including all accessories (rotating nozzle, brush...) that may degrade the surface condition of the products.*



## CONSUMPTION OF INSTALLATION PRODUCTS

- **GLUE:** ORFLEX Hautes Performances: **7 to 8 kg/m<sup>2</sup>** indoors and **8 to 10 kg/m<sup>2</sup>** outdoors
- **PROTECTION:** Water-repellent (outdoors or in damp rooms): **9 m<sup>2</sup>/L**

*Information given for guidance only for the selected collection of facing stones.  
For more details: [www.orsol.fr](http://www.orsol.fr)*



BIT.LY/ORSOL-TUTO-POSE-PLAQUE

## LAYOUT OF THE OLYMPE COLLECTION



1 install



2 remove any excess adhesive



3 apply the water-repellent

**Layout** = Way of arranging the facing stone elements to obtain a harmonious whole.

### LAYOUT OF CORNERS:

- The corners must be installed before the facing stone. They must be glued at a rate of 1 lm per day.
- Glue the corners from bottom to top, swapping short and long sides from one row to the next and leaving a 2 mm joint between each corner.

### LAYOUT OF FACING STONES:

- OLYMPE facing stones have different shapes and sizes compatible with each other. This facing stone makes it possible to carry out 2 types of installation:
  - in-line installation
  - opus installation.

We recommend that you carry out a trial installation on the floor before you start gluing. This will give you time to practise and ensure that the rules for installing this cladding according to the chosen layout are respected.

#### IN-LINE INSTALLATION



- Glue the facing stones of the same height in the direction of their length leaving a 2 mm joint between each stone.
- Cross the vertical joints from one row to the next.

#### OPUS INSTALLATION



- Glue the facing stones randomly lengthwise leaving a 2 mm joint between each stone.
- Do not make vertical joints more than 25 cm high.
- Avoid horizontal alignments of more than 1 lm.

## TO ORDER

	Reference		Packaging		Average weight (kg)	
	Natural	Clay earth	Package	Pallet	Package	Pallet
Facing stone	POL5	POL10	1 paquet (± 0,25 m <sup>2</sup> )	80 paquets (± 20 m <sup>2</sup> )	13,30	1089
Corner	AOL5	AOL10	1 paquet (± 0,3 ml)	32 paquets (± 9,6 ml)	8,40	283

NOTE: We recommend that you supply the site all at once to ensure uniformity of the hues.