




PORTLAND Collection

FACING STONE
WITHOUT JOINT




CRSOL
ÉMOTIONS MINÉRALES

HUES



Natural**



Light grey**



* Non-contractual hues

** Chromatic variations (see overleaf)

PRODUCTS



Facing stone
L. 42 x h. 20 Overall length 47
Thickness 2 cm
Average weight : 31,5 kg/m²

CHARACTERISTICS

- Panel facing stones, assembly of long stones, gentle reliefs
- Compatible for installation on ETI and siding
- Through-coloured
- Frost-resistant



CHROMATIC VARIATIONS

ORSOL products have varying degrees of shades from one hue to another. Refer to the following symbols for the degree of shade of each hue.



Example: the natural tone offers a richer degree of colour and patina (different shades from one stone to another) than the stone tone, which is more uniform. Variations in shade on a stone or from one stone to another inherent to the natural appearance of the products cannot be the subject of a complaint.

INSTALLATION OF FACING STONES

Download our [technical specifications](#) to identify your substrate, find out the authorised height of installation and for installation information. Only by complying with the recommendations described in this process will you be entitled to the ORSOL [10-year product guarantee](#).



TECHNICAL SPECIFICATIONS

Download the TECHNICAL SPECIFICATIONS at www.orsol.fr



Link to the document library: <https://www.orsol.fr/ressources/documenttheque>

PRECAUTIONS FOR USE

Check the conformity of the products and their packaging immediately upon receiving them, as complaints about the appearance of the products must be made before installation. Our liability is limited solely to the replacement of defective products (see our *General Terms and Conditions of Sale* available at www.orsol.fr).

In order to obtain a good aesthetic rendering, it is advisable to supply your sites in one go and to mix the contents of the different packages and pallets during their use; this mixture will reinforce the natural appearance of the products by harmonizing the colours and shades.

MAINTENANCE

Neomineral is a material of 99% mineral origin, which lives, breathes, and perspires according to its environment. To provide the facing stones with lasting protection, it is essential to **apply a water-repellent product** to limit the impact of external aggression. This treatment should be applied to a clean, dry product after installation, and may need to be **renewed every 5 years**.

Do not use high-pressure or steam cleaners, including all accessories (rotating nozzle, brush...) that may degrade the surface condition of the products.



CONSUMPTION OF INSTALLATION PRODUCTS

- **GLUE:** ORFLEX Hautes Performances: **7 to 8 kg/m²** indoors and **8 to 10 kg/m²** outdoors
- **PROTECTION:** Water-repellent (outdoors or in damp rooms): **9 m²/L**

*Information given for guidance only for the selected collection of facing stones.
For more details: www.orsol.fr*

LAYOUT OF THE PORTLAND COLLECTION



BIT.LY/ORSOL-TUTO-POSE-PLAQUE



1 | install



2 | remove any excess adhesive



3 | apply the water-repellent

Layout = Way of arranging the facing stone elements to obtain a harmonious whole.

LAYOUT OF CORNERS:

- The PORTLAND collection does not include a corner accessory. However, if your wall has corners that need to be dressed, these can be done using the facing. For their installation, please refer to the [Technical Specifications](#).
- The corners must be installed **before** the facing stone. They must be glued at a rate of 1 linear metre per day.

LAYOUT OF FACING STONES:

- Cut the starter panel to obtain a straight side.
- Glue the facing stones from bottom to top in rows of 2 or 3 heights while crossing the panels from one row to the other
- To avoid vertical alignments from one row to the next, other starter panels will need to be cut to different lengths.
- Continue the wall along its entire length.



TO ORDER

	Reference		Packaging		Average weight (kg)	
	Natural	Light grey	Package	Pallet	Package	Pallet
Facing stone	PPOR5	PPOR12	1 package (± 0,33 m ²)	84 packages (± 27,7 m ²)	12,00	1027

NOTE: We recommend that you supply the site all at once to ensure uniformity of the hues.